

Stage 3

Stage 4

Stage 5

Henson

Leading the field



Technical specification



Henson 9000 Perimeter: Technical specification

Test specifications

Visual field test range	60° (monocular) / 160° (binocular) 10,000 ASB 31.5 ASB
Visual field testing distance	25 cm
Stimulus intensity (maximum)	10,000 ASB
Background illumination	31.5 ASB
Stimulus duration	200 ms
Stimulus size	Goldmann III

Test methods Standard Automated Perimetry (SAP), white-on-white

Screening tests/patterns

Smart Supra - single stimulus	26, 54 and 86 point tests (incorporating both 24-2 and 10-2 test pattern points)
Smart Supra - multiple stimulus	26, 54 and 86 point tests (incorporating both 24-2 and 10-2 test pattern points)
Esterman (Driving)	Groups 1 (120 point) and 2 (124 point) (EU standard)
Customized tests	Test locations can be manually added to all Smart Supra screening tests

Threshold tests/patterns

ZATA Standard - threshold central	10-2; 30/24-2 (extendable in-test)
ZATA Fast - threshold central	10-2; 30/24-2 (extendable in-test)

Average test times*

Smart Supra – single stimulus	~1 min (26 points); ~3.5 minutes for fully extended 24-2 plus 10-2 test (86 points)
Smart Supra – multiple stimulus	Under 30 seconds (26 points)
ZATA	~2.5 minutes per eye
ZATA Fast	~ 2 minutes per eye

Fixation control

Fixation target	Single or 4-point LED diamond pattern
Heijl-Krakau	Yes (ZATA)
Video eye monitor	Yes

Software features

Patient management database	MS Windows compatible; networkable
Practice management integration	EMR compatibility (parameter passing and text file)
Languages	English, Chinese, French, German, Italian, Japanese, Norwegian, Portuguese, Brazilian Portuguese, Spanish (Latin America), Spanish (Peninsula)
Hemifield analysis	Yes
Progression analysis	Yes
HFA data import	Yes

Connectivity

DICOM	Yes (images)
Ethernet	Yes, via connected computer
Database backup	Removable, network or cloud storage

Dimensions

Weight (kg)	13.5
Size, W x D x H (mm)	440 x 400 x 452

Classification

Medical device	Class 1
Applied part	Type B
Control device	External PC / laptop / tablet running MS Windows® Professional, v. 7, and above
Patient unit inputs/outputs	C13 mains input; Patient Response Button; 2 x USB Type B connector
Electrical requirements	85 – 263 V AC, 50/60 Hz, 60 VA
Optional printer	Any compatible with controlling computer

*Test times are approximations only and will differ according to patient response time and level of loss.

© Elektron Eye Technology Ltd. All rights reserved. Microsoft® and Windows® are either registered trademarks or trademarks of Microsoft Corporation® in the United States and/or other countries.

For more information visit elektron-eye-technology.com/products/henson-9000-perimeter/
TS H9000 V-2.1 (12-18)

